

Otago District.

Catlin's—Waikawa Road—

Earthworks—

Formation, &c. (according to length of lead)	...	s. d. 0 10	to	s. d. 1 2	per cub. yd.
Soft rock				0 10	"
Hard rock		1 3	to	1 9	"
Culverts, including all excavations	..	{ 2 6	"	3 0	per lin. ft.
		{ 3 6	"	4 0	
Stumping (average rate)				25 0	per ch.

Catlin's River Road—

Earthworks—

Formation (including stumping)		s. d. 30 0	to	s. d. 40 0	per ch.
Side-cutting (including stumping)		0 11	"	1 0	per cub. yd.
Block-cutting (according to length of lead)		1 0	"	1 6	"
Rock-cutting	...	1 9	"	2 6	"

Culverts—

12in. by 12in.		4 0	"	5 0	per lin. ft.
18in. by 18in.				6 6	"
24in. by 24in.				7 6	"

Taukupu Valley Road—

Logging-up (according to the nature of the timber to be logged up, the logging was 40ft. wide)		10 0	to	15 0	per ch.
---	--	------	----	------	---------

Public Works Office,
Wellington, 29th September, 1892.

H J H. BLOW,
Under-Secretary for Public Works.

[*Approximate Cost of Paper*:—Preparation, £10; printing (1,160 copies), £3 5s.]

By Authority GEORGE DIDSBURY, Government Printer, Wellington.—1892.

Price 6d.]