

No. 4.—RETURN of NOTICES given to FENCE OR REPAIR DANGEROUS PARTS of MACHINERY, &c.—  
continued.

| Number. | Machinery.        | Particulars.                                                 |
|---------|-------------------|--------------------------------------------------------------|
| 1       | Electric lift     | New worm-wheel.                                              |
| 3       | "                 | Safety grips overhauled and adjusted.                        |
| 2       | Electric lighting | Belting and shafting.                                        |
| 1       | "                 | Gate fitted to approaches.                                   |
| 1       | "                 | Platform, railing, and ladder.                               |
| 1       | "                 | Top of water-race covered.                                   |
| 1       | "                 | Side of main driving-belt.                                   |
| 7       | Electric motor    | Belting.                                                     |
| 1       | "                 | Belting fenced in form of box.                               |
| 1       | "                 | Cased in, leaving openings for belting from driving-pulley.  |
| 1       | "                 | Driving-pulley.                                              |
| 1       | "                 | Fenced all round.                                            |
| 1       | "                 | Hand-rail and step to crane secured.                         |
| 1       | "                 | Hatch railed in.                                             |
| 5       | "                 | Main driving-belts.                                          |
| 4       | "                 | Wheel of machine.                                            |
| 2       | Engineer's shop   | Emery wheel.                                                 |
| 4       | "                 | Fence round engine.                                          |
| 4       | "                 | Fly-wheel of engine, and driving-belt.                       |
| 1       | "                 | Machinery and belting.                                       |
| 2       | "                 | Pulley and driving-belt.                                     |
| 1       | "                 | Stone, and emery wheel.                                      |
| 1       | "                 | Strong railing fitted at side of engine.                     |
| 1       | Fellmongery       | Engine and machines.                                         |
| 1       | "                 | Emery wheel.                                                 |
| 1       | Firewood-cutting  | Belting and side of driving-pulley.                          |
| 2       | "                 | Crosscut-saw guarded over the top by means of a sliding box. |
| 1       | "                 | Engine fenced in all round.                                  |
| 1       | "                 | Key-head in pulley, and end of shaft, and belting.           |
| 1       | "                 | Side of driving-pulley, and main driving-belt.               |
| 2       | Flax-mill         | Belting.                                                     |
| 1       | "                 | Belting, shafting, and pulleys.                              |
| 2       | "                 | Belting and end of shaft.                                    |
| 3       | "                 | Belting and machinery.                                       |
| 2       | "                 | End of shaft.                                                |
| 1       | "                 | Grating in water-race made closer and wheel guarded.         |
| 1       | "                 | Grating fitted and water-race covered.                       |
| 6       | "                 | Machines and end of shafting.                                |
| 1       | "                 | Railing at doorway, front of chaff-cutter.                   |
| 1       | "                 | Scutcher put in order.                                       |
| 1       | "                 | Shafting, pulley, belting, and wheel guarded.                |
| 1       | "                 | Shafting for scutcher and mouth of scutcher strengthened.    |
| 2       | "                 | Strengthened mouth of scutcher and, reduced width of mouth.  |
| 1       | "                 | Strong appliance for changing belts to twin saws.            |
| 1       | "                 | Water-wheel and side of belt-pulley.                         |
| 1       | Flock-mill        | Driving-wheels.                                              |
| 1       | Fly-wheel         | New key fitted and side guarded.                             |
| 2       | Gas-engines       | Belting and machinery.                                       |
| 5       | "                 | Belting fenced all round.                                    |
| 2       | "                 | Counter-shaft.                                               |
| 2       | "                 | Crank-shaft and fly-wheel.                                   |
| 5       | "                 | Driving-pulley, and belt-pulley of collar-rollers.           |
| 7       | "                 | End of crank-shaft.                                          |
| 20      | "                 | Engine and shafting.                                         |
| 1       | "                 | Engine and dynamo.                                           |
| 6       | "                 | Fence in all round.                                          |
| 1       | "                 | Fencing of fly-wheel renewed.                                |
| 26      | "                 | Fly-wheel of engine.                                         |
| 4       | "                 | Fly-wheel and side of engine.                                |